

SMALL MOTOR, SMALL VIBRATION MOTOR, AND PORTABLE INFORMATION APPARATUS

Publication number: JP2003174753

Publication date: 2003-06-20

Inventor: SUZUKI TOSHIO; HOSHIBA TAKANOBU

Applicant: NAMIKI PRECISION JEWEL CO LTD

Classification:

- international: B06B1/04; B06B1/16; H02K5/22; H02K7/06; H02K7/065; H02K23/58; H02K5/00; B06B1/02; B06B1/10; H02K5/22; H02K7/06; H02K23/58; H02K5/00; (IPC1-7): H02K5/22; B06B1/04; B06B1/16; H02K7/065; H02K23/58

- European: H02K5/22B; H02K7/06B

Application number: JP20010370569 20011204

Priority number(s): JP20010370569 20011204

Also published as:

- EP1463180 (A1)
- WO03049254 (A1)
- US7265465 (B2)
- US2005046302 (A1)
- CN1599969 (A)

[more >>](#)


[Report a data error here](#)

Abstract of JP2003174753

PROBLEM TO BE SOLVED: To miniaturize the whole motor, and positively perform electrical connection through an engaging terminal by enabling easy assembly of the motor itself.

SOLUTION: An insulating-resin terminal block body 18 to be fitted in and secured is provided on one end of a motor housing 10, and a pair of supporting pins 21a, 21b are protruded in the roughly parallel direction with a plate surface of a printed circuit board P and supported by the terminal block body 18. Respective leads 171 of a motor driving circuit are guided outward from the terminal block body 18. Central spiral parts 200 are fitted on the axial lines of the supporting pins 21a, 21b. A pair of torsion springs 20a, 20b are provided as engagement terminals with one spring end 201 taken as a contact point with a feeding land R of the printed circuit board P, and the other spring end 202 taken as a contact point with a lead of the motor driving circuit.

COPYRIGHT: (C)2003,JPO



Data supplied from the esp@cenet database - Worldwide